


LOAD CHART FOR TADANO TG450 45 TON

Outriggers Fully Extended

RADIUS IN METER	MODE 1			MODE 2		MODE 3
	BOOM	BOOM	BOOM	BOOM	BOOM	BOOM
					5°	30°
3.0	45.0	27.0			2.50	1.00
3.5	40.5	27.0			2.50	1.00
4.0	36.5	27.0			2.50	1.00
4.5	33.0	27.0	18.0		2.33	1.00
5.0	30.2	27.0	18.0		2.06	0.96
5.5	27.5	24.9	18.0		1.78	0.90
6.0	25.0	22.9	18.0		1.62	0.87
6.5	22.7	21.2	18.0		1.48	0.84
7.0	20.0	19.5	16.7	12.0	1.32	0.80
7.5	17.8	17.8	15.6	12.0	1.18	0.76
8.0		15.6	14.7	12.0	1.00	0.74
9.0		12.8	12.8	10.7	0.77	0.69
10.0		10.5	10.4	9.7	0.50	0.43
11.0		8.6	8.5	8.9		
12.0		7.1	7.1	8.0		
14.0		5.0	5.0	5.8		
16.0		3.5	3.5	4.3		
18.0			2.4	3.2		
20.0			1.5	2.4		
22.0			0.7	1.7		
24.0				1.1		
26.0				0.6		
28.0						
30.0						




V.A. Taklikar
 Competent Person
 (CPC No. T-018/2013)